Product profile

7X1

Mobile Computers

- Highly configurable and upgradeable, allowing up to 3 integrated wireless communication options in the same device
- Part of a proven and comprehensive solution set including mobile printers, centralized system and device management products, peripherals, and accessories
- Combines the power and speed of the Intel[®] XScale[™] processor and the Microsoft[®] Windows Mobile for Pocket PC operating system
- Available with either integrated imaging or laser scanning technologies
- Large, transflective color display provides crisp, vivid screen for high contrast both indoors and out
- Numeric and full alphanumeric keypad options





741B / 751B / 761B Color

Rugged Enterprise Mobility

Whether on the road, in the field, or on the factory floor, mobile workers demand rugged, reliable tools to do their jobs. Bringing updated technologies to the front-line worker, the Intermec® models 741, 751 and 761 mobile computers build on the proven, unprecedented success of the 700 Color Series. Designed from the ground up for use in harsh environments, the 700 device can withstand multiple 6-ft. (1.8 m) drops to concrete and is sealed against rain and dust. The ergonomic case design is sculpted and balanced, maximizing user comfort during long-term use. Radio and scanner options are integrated, not add-ons, which means they are tested to the same ruggedness standards, and don't compromise the environmental or functional characteristics of the unit.

Scaleable, Comprehensive Package In addition to the large, brilliant color display, Intel® XScale[™] processor, and Microsoft[®] Windows Mobile[®] for Pocket PC, the 700 Series' customer configurable design allows the integration of up to three radios (WLAN, WWAN, Bluetooth) in a single device. On-board wired Ethernet is standard on the 700 Series, and unlike many competitive devices, true Ethernet speeds are maintained. In addition, the built-in Flash ROM folder allows permanent storage of applications, drivers and startup files on non-volatile flash memory. In addition, Intermec's ReadiCareSM Deployment Services provide WWAN activation, provisioning and logistics control so that the 700 Series customer is up and productive "right out of the box".

GPRS/EDGE only

Data Collection

Offering both laser and imaging scanning options, Intermec's imaging technologies further enable device capabilities by enabling: omni-directional decoding – eliminating the need to line up the scan beam perpendicular to the bars ; image capture – allowing for the storage of black and white photographs and signatures for applications such as proof of delivery, market surveys and field inspections; as well as decoding standard linear 1D, 2D matrix, stacked and composite barcodes.

Cross Functional Deployments

Whether your application is stand-alone, client-server, browser-based, or terminal emulation, the 700 Color is the right tool for the job. It's comprehensive feature set allows for a single device to provide cross functional capabilities. Your day's start-up activates can begin on-premise, utilizing wireless LAN access points for cross docking or load planning applications and move off-premise to the delivery vehicle, utilizing wireless wide-area voice and data services, all the while using Bluetooth compatible networking to print. Whatever your communication requirements, the 700 Color has you covered.

Complete Systems That Work

The 700 Color is part of a suite of fully- integrated system components, including a wide selection of peripherals and accessories. Intermec systems are designed to meet the needs of the business enterprise. Applications and communication software products are available to address business process automation needs – including software to remotely configure and manage devices from a central location. The Intermec 700 Color can help businesses worldwide improve their operations, increase mobile worker efficiency, and build a better bottom line.

Portable Receipt Printers



- Rugged design built for field environment
 2" and 4" paper options
- Lightweight, belt-clip mounting for hands-free mobility
- Bluetooth compatible wireless printing, IrDA and RS-232 serial communications
- Rechargeable customer replaceable, Lithium-Ion battery provides ample power for all-day printing
- Wireless IrDA interface to mobile computer

Physical Characteristics for models PB40 and PB41 Dimensions:

167mm L x 172mm W x 66mm D 6.56in L x 6.8in W x 2.6in D **Weight:** 932 gms (32.9 oz) with batteries and paper)

Physical Characteristics for models PB20 and 681T Dimensions:

144mm Lx 112mm W x 616mm D 5.65in L x 4.39in W x 2.40in D Weight: 393g (13.85 oz) without paper; 418g (14.72 oz) with paper

Workboards



- One-piecedesignholds700seriessecurelywhile providing 2" or 4" printer receipts
- Lightweight, rugged and weather resistant
 SelfpoweredwithLithium-lonbatterytosupport
- all day printing need
- Supports user downloadable character sets
- 4 Mbits of flash memory
- Power saving sleep mode

Physical Characteristics for model 782T Dimensions:

290mm L x 213mm W x 67mm H 11.42in L x 8.40in W x 2.63in H **Weight:** 815.4g (28.76oz) without paper; the weight with paper is 29.63 oz. 840 gms or 30.48 oz

Physical Characteristics for model PW40

Dimensions: 21 cm L x 35.25 cm W x 6.7 cm H 8.24 in L x 13.9 in W x 2.62 in H Weight: 1.13 kg (2.51 lbs.) without paper; 1.39kg (3.07 lbs.) with paper

Vehicle Dock and Cradle (shown with stand)



- Provides a secure place to store the 700 Series mobile computer in a vehicle or fork truck
- Full access to touch screen and all keys while in dock
- One-handed insertion and removal
- Two RS-232 ports for connectivity via DB-9 connector to printers and other serial devices, including long range scanners
- Option for DC power jack to support charging of the mobile computer

Physical Characteristics

Dimensions: 159mm L x 111mm W x 58mm D 6.25in L x 6.25in x 2.3in D Weight: 284g (10oz)

Vehicle Dock and Cradle



- Ideal for home and small depot environments
- Charges the 700 Series mobile computer
- Supports RS-232 serial port with DB-9 connector, Active Sync cable and printers; Ethernet 10Base-T LAN; or USB host.

Physical Characteristics

Dimensions: 114mm L x 133mm W x 64 mm 4.5in L x 5.25in W x 2.5in D Weight: 1181g (2.6lb)

Multi-unit Depot Dock



- Holds four Intermec 700 Series mobile computers for charging and communications
- Fullaccesstotouchscreensandallkeyswhileindock
 Fullaccesstotouchscreensandallkeyswhileindock
- Ethernet 10/100 Base-T LAN connectivity with integrated switch or charge only option
 - Can be mounted on a countertop or wall

Physical Characteristics

Dimensions: 114mm L x531mm W x61mm D 4.5in L x 20.9in W x 2.4in D Weight: 1658g (3.65lb)

Scan Handle



- Attaches to 700 Series without extra tools; designed for easy insertion and removal
- Handle option to allow for docking with handle attached.
- Ergonomically designed handle and trigger mechanism allows for fatigue-free use
- 700 is positioned horizontally for convenient access to display and keypad
- Access to the 700 Series battery compartment allows the user to change the battery pack without removing the handle

Physical Characteristics (with 700 installed)

Size: 3.7" x 7.5" x 1.7" (94x191x43mm) plus 2.0" x 4.6" x 1.1" (51x117x28mm) volume at base of the handle for the handle grip (handle and handheld overall dimensions)

Weight: 624g (22oz)

Adapter Modules

The 700 Series adaptation of snap-on modules accessories easily enables applications requiring support for long-range scanning; mag stripe reading (MSR) and dial-up modem capabilities.

Mag Stripe Reader*



- Reads cards up to .055 inches (1.4 mm) thick
- Supports ANSI, ISO, AAMVA, CA DMV and User Configurable Generic Formats
- Snap on retainment features for temporary attachment
- Thumb screws for semi-permanent attachment
 Ability to charge unit via cable or dock while adapter
- is attached.Battery accessible with module attached

Dimensions:

3.55in W x 3.25in L x 1.45in D

*The Mag Stripe Reader is NOT RoHS certified.

3.3 Volt to 5 Volt Scanner Adapter



- 3.3 Volt to 5 Volt Boost converter with DB9M RS-232 interface
- Snap on retainment features for temporary attachment
- Attachable with thumb screws for semi-permanent attachment
- Battery accessible with module attached

Dimensions:

3.52 in W x 2.63in L x 1.39in D

Snap-On Modem



- SupportsV.90fordownloadspeedsupto56Kbps
- LED's to indicate connection status
- Connects to a standard RJ-11 phone jack
- Battery accessible with module attached
- Ability to charge unit via cable while adapter is attached.

Dimensions: 3.55in W x 3.45in L x 1.45in D

Accessories



The Intermec 700 series support a full line of accessory items including: holsters, carry cases, multi-pack external battery charger, power and data cables, compact flash and secure digital cards.

Physical Characteristics

Length: 191 mm (7.53 in.) Width: 90 mm (3.5 in.) Height: 50 mm (1.97 in.) Weight: 483-568 grams (17-20 oz) depending on options

Environmental

Operating Temp: -20° to +60°C (-4° to +140°F) **Storage Temp:** -20° to +60°C (-4° to +140°F) **Relative Humdity:** 5% to 95% (non-condensing) **Rain and Dust Resistance:** IP64 compliant **Drop Spec:** 6 ft., (1.8 meter) MIL-STD 810F

Power

Battery Type: Lithium-Ion, 7.2V, 2400 mAh, customer replaceable Battery Capacity: 17.3 Watt-hours Battery Life: 9-12 hours, application dependent Recharging Time: 4 hours

Operating Systems

Microsoft° Windows° for Pocket PC Windows Mobile° 2003 Windows Mobile° 5.0 (741B & 751B models only)

Microprocessor Intel[®] XScale[™] Processor, 400 MHz

Memory and Storage

RAM Memory: 64 MB (128 MB optional) Flash ROM: 64 MB; includes ROM folder for application storage

Internal Slots • Secure Digital (SD)

• CompactFlash (CF) Type II

Display

Transflective, 240x320 pixels, 3.8 in. (97 mm) diagonal, 256 K colors

Standard Communications

RS232 IrDA 1.1 (115 kbps) 10/100 Base-T Ethernet USB Client

Integrated Radio Options

LAN: 802.11b/g (Wi-Fi certified) WAN: GSM/GPRS/EDGE, CDMA/1xRTT Bluetooth®

Modem

- Optional v.90 modem snaps on to 700 Color
- v.92 docking options

Integrated Scanner Options

- Area imager
- Linear imager
- Standard Range laser

Keypad Options

- NumericFull alphanumeric
- i un alphanumen

Cisco Compatible

Version 1 Version 2

ReadiCare[™] Activation and

Provisioning Services WWAN Carrier Provisioning WWAN Carrier Activation Software Configuration Tagging Operational Testing Packing, Storage & Staging

For additional details, go to:

http://www.intermec.com/ WWANActivationandProvisioning

Regulatory Approvals

FCC Part 15 Class B UL Listing CE Mark CB Report

Hazardous Location Certified (741 & 751 models only) UL Listing (United States and Canada)Division 2, Class

I, Groups A, B, C, D

ATEX Directive (741 & 751 models only)

Zone 2, IICEEx nL IIC T6 UL 3' Drop Specifications IP40 Compliant **Operating Temp:** -10° to +40°C (+14° to +104°F)

* Bluetooth is a trademark owned by Bluetooth SIG, Inc., USA.

Microsoft, Windows, the Windows logo, Windows Media, Outlook, and ActiveSync are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

 Intel° and $\mathsf{XScale}^{\tilde{}}$ are trademarks of Intel Corporation.



JTION -Fight when some soft taxe into beam. ATTENTION-Lamilies item into beam. Taxwerkan no pee segment flammart dans in belance.

.1|1.1|1. CISCO. Competible







Copyright © 2007 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



LOGICODE SA Str. Mihai Românu nr. 5B, 400495 Cluj-Napoca Tel: 0364 409108, 0731307621 informatii@logicode.ro www.logicode.ro

